



OOO «Torgoviy Dom «Lesokhimik»  
11 Sedova Street, St. Petersburg, 192019, Russia  
Tel/fax: +7 812 38 061 77

## MATERIAL SAFETY DATA SHEET

### 1. Product Identification

**DISTILLED TALL OIL**

### 2. Manufacturer

JSC Segezhskiy Pulp and Paper Mill  
1, Zavodskaya str., 186420, Segezha, Karelia, Russia

### 3. Supplier

OOO «Torgoviy Dom «Lesokhimik»  
11 Sedova str., 192019, Saint-Petersburg, Russia  
Phone/fax: +7 812 38 061 77

### 4. Hazard Identification

Irritation of skin, eyes and respiratory tract

### 5. Emergency and First-Aid Procedures

**Ingestion:** Rinse mouth with water. Seek medical advice if irritation persists. **DO NOT** induce vomiting because of risk of aspiration

**Eye Contact:** Rinse immediately with plenty of water. Eyelids should be held away from the eyeball to ensure thorough rinsing. Seek medical advice if irritation persists

**Skin contact:** Wash with soap and water. Seek medical advice if irritation persists.

### 6. Fire and Explosion Data

**Extinguishing Media:** Water fog or mist, foam, dry chemical, or carbon dioxide.

**Special Firefighting Procedures:** Avoid using a direct stream of water, other than light spray.

**General Fire Hazards:** Porous material such as rags, paper, insulation, or organic clay may spontaneously combust when wetted with this material. If mist is generated, minimum flash point may be reduced.

**Unusual Fire and Explosion Hazards:** Toxic gases may be released during fire. Smoke, carbon monoxide, carbon dioxide, water, trace quantities of sulfur oxides, and other products of combustion.

**Fire Fighting Equipment:** Wear full protective clothing, including self-contained positive pressure or pressure demand breathing apparatus, helmet, and protective clothing. Use water spray to cool fire-exposed containers and to protect personnel.



ООО «Торговый Дом «Лесохимик»  
11 Sedova Street, St. Petersburg, 192019, Russia  
Tel/fax: +7 812 38 061 77

## 7. Accidental release measures

**Personal precautions:** Put on adequate protective equipment.

**Environmental precautions:** Keep away from drains, surface-water, ground-water and soil.

**Methods for cleaning up:** Collect as much as possible in a container for disposal. Cover the remainder with inert absorbent. Disposal according to local regulations. Can self-ignite when soaked into porous material (eg. rags, textiles, insulations, inorganic materials).

## 8. Rules of the reference and storage

**Handling:** Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid inhalation of mists/vapors/fumes. Keep this product from heat, sparks, or open flame. Do not use air pressure or apply heat with open flame to remove contents of drum. After emptied, drum may retain solid, liquid and/or vapor residues. Continue to observe all precautions on label as if drum were full. Do not cut, puncture, torch or weld on or near the emptied drum. Do not use for other purposes. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet or applying cosmetics.

**Storage:** Store at ambient temperature and atmospheric pressure. Porous material such as clothing, rags, paper, insulation, or organic clay may spontaneously combust when wetted with this material.

## 9. Exposure controls/personal protection

**Respiratory protection:** Suitable respiratory equipment in case of insufficient ventilation

**Hand protection:** Protective gloves. PVC

**Eye protection:** Safety goggles

**Skin and body protection:** Apron, boots, face shield, or rubber suit may be needed when handling large amounts.

**Work:** Eyewash stations and safety showers should be readily accessible. Provide local exhaust as needed. Provide general ventilation in processing and storage areas. Self-contained breathing apparatus (SCBA) recommended when fighting fire.

## 10. Physical/Chemical Properties

**Color and odor:** Yellow liquid with mild odor of vegetable oil and pale yellow sediment which becomes transparent at 80°C

**Density:** 950 kg/m<sup>3</sup> (20°C)

**Boiling point:** > 200°C

**Solubility in water:** Insoluble

**Flash point:** > 200°C



ООО «Торговый Дом «Лесохимик»  
11 Sedova Street, St. Petersburg, 192019, Russia  
Tel/fax: +7 812 38 061 77

## 11. Stability

**Chemical Stability:**

This product is stable

**Conditions to avoid:**

Avoid strong oxidizing agents, acids, bases.

Avoid contact with porous materials.

Excessive heating and open flame

**Hazardous decomposition products:**

Carbon dioxide, carbon oxides

## 12. Toxicity

Will cause irritation due to skin/eye/ingestion contact

## 13. Environmental protection

It is necessary to avoid contact of substance with drinking sources.

The product possesses light toxic action on fishes and water micro flora of natural reservoirs.

## 14. Disposal considerations

**Methods of disposal:** Disposal according to local regulations. Controlled incineration.

## 15. Transport information

Able to be transported by aircrafts, railway wagons and vehicles non specially equipped.

## 16. Regulatory information

Not classified

## 17. Additive information

Product should be transported in polyethylene, polypropylene, aluminum or stainless steel containers

**Product has manufactured according TU 13-00281074-26-95**

**Guaranty shelf life – 4 months from date of production**